


IMPORTANT LIFE SAFETY PRODUCT NOTE
 PF-2248CF-SC-13-6.5 (OPTIONAL)
 TO ACHIEVE RATING, 2-HOUR FIRE BARRIER
 MUST BE INSTALLED IN THE JOINT OPENING
 WHOSE JOINT FACE IS RATED FOR 2-HOUR.
 BARRIERS MUST BE INSTALLED IN STRICT
 ACCORDANCE WITH TYPICAL FLOOR FIRE
 BARRIER INSTALLATION INSTRUCTIONS
 PROVIDED IN THIS SUBMITTAL.
INTERTEK DESIGN NO. MM/EJH 120-03

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
RXH-13-6.5	13"	6.5"	9.75"	16.25"	19.25"	12.75"	EJMR1025
RXH-13-6.5 w/ PF-2248CF-SC-13-6.5	13"	6.5"	9.75"	16.25"	19.25"	12.75"	EJMR1025

Representative:	Customer:	Project:	Location:	Project Number:
-----------------	-----------	----------	-----------	-----------------



MM SYSTEMS
 50 MM WAY
 PENDERGRASS, GA. 30567
 PHONE: 706-824-7500
 800-241-3460
 FAX: 706-824-7501
www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN
 All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

RXH-13-6.5

Model:		
Drawn by:	LMP	Scale: NTS
SHT. . OF .	Issue Date: 09-15-15	Drawing Number: EJMR1025