



IMPORTANT LIFE SAFETY NOTE
 SLAB THICKNESS AND CONSTRUCTION TO MEET HOURLY ENDURANCE REQUIRED. REFER TO IBC TABLE 721.2.2.1 "MINIMUM SLAB THICKNESS".

IMPORTANT LIFE SAFETY NOTE
 PF-2248CF-SC-21-21 (OPTIONAL) MUST BE INSTALLED IN THE JOINT OPENING WHERE JOINT FACE IS RATED FOR 2-HOUR. BARRIERS MUST BE INSTALLED IN STRICT ACCORDANCE WITH TYPICAL FLOOR FIRE BARRIER INSTALLATION INSTRUCTIONS PROVIDED IN THIS SUBMITTAL.
 INTERTEK DESIGN NO. MMJEH-120-03

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
PDS-2100-100-2.25H	21"	2.5"	20.25"	21.75"	42"	39.5"	EJNB5076
PDS-2100-100-2.25H w/ PF-2248CF-SC-21-21	21"	5"	20.25"	21.75"	42"	37"	EJNB5076

SIGHT LINE MATCHES PDSE-2100-50-2.25H

Representative: - Customer: - Project: - Location: - Project Number: -



50 MM WAY
PENDERGRASS, GA. 30567
PHONE: 706-824-7500
800-241-3460
FAX: 706-824-7501

www.mm.systems

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems and hereby reserved and are not to be reproduced or provided to any other party. MM Systems reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Drawn by: BOO
 Scale: NTS
 Issue Date: 08-25-21
 SHT. 1 OF 1

Drawing Number:
EJNB5076

For Spec-Data, Installation Guides, or movement requirements, contact MM Systems