



S4 CLIP - SPRING STEEL  
 @ 24" O.C. [610mm]  
 ALTERNATE OFFSET 180°  
 9342  
 1/4" - 20 X 1" FHMS/SS  
 @ 24" O.C. [610mm]  
 9362

Model	Nominal "JT"	Joint Opening "JT"			Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.	
SN-200	2"	1.375"	1.5"	2.5"	3"	SM1702
						1.625"

FIRE BARRIER IS NOT AVAILABLE FOR THIS MODEL

ARCHITECT/CONTRACTOR NOTE:  
 ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative: \_\_\_\_\_ Customer: \_\_\_\_\_ Project: \_\_\_\_\_ Location: \_\_\_\_\_ Project Number: \_\_\_\_\_



**MM**  
 MM SYSTEMS

50 MM WAY  
 PENDERGRASS, GA. 30567  
 PHONE: 706-824-7500  
 800-241-3460  
 FAX: 706-824-7501

www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

**RIGHTS OF DESIGN**

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Model:

**SN-200**

Drawn by:

CEL

Scale:

NTS

SHT. OF

Issue Date:  
 11-12-18

Drawing Number:

**SM1702**