

1/4" X 1 3/4" PFH SILVER TAPPER
@ 24" O.C. [610mm]
9406

1/4" X 1 3/4" PFH SILVER TAPPER
@ 24" O.C. [610mm]
9406

1/8" X 1" STAINLESS STEEL
HOLDDOWN STRIP


20 MIL MOISTURE
BARRIER (OPTIONAL)

IMPORTANT LIFE SAFETY PRODUCT NOTE
PF-2018F-SC-2-1
TO ACHIEVE RATING, 2-HOUR FIRE BARRIER
MUST BE INSTALLED IN 2-HOUR RATED SLAB,
MINIMUM 4-1/2" JT. FACE. BARRIERS MUST BE
INSTALLED IN STRICT ACCORDANCE WITH
TYPICAL FLOOR FIRE BARRIER INSTALLATION
INSTRUCTIONS PROVIDED IN THIS SUBMITTAL.

IMPORTANT LIFE SAFETY NOTE
4-1/2" MINIMUM FACE OF SLAB (AS SHOWN)
REQUIRED FOR OPTIONAL FIRE RATING TO
BE AVAILABLE IN ACCORDANCE TO IBC
TABLE 721.2.2.1 "MINIMUM SLAB THICKNESS"
ARCHITECT / CONTRACTOR MUST VERIFY
PRIOR TO FABRICATION.

* CONTACT FACTORY FOR OTHER STYLES OF FIRE BARRIER

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
SP-SS-2-1_2HFPF	2"	0.875"	1.5"	2.5"	3"	2.125"	

Representative:	Customer:	Project:	Location:	Project Number:	
 MM SYSTEMS 50 MM WAY PENDERGRASS, GA. 30567 PHONE: 706-824-7500 800-241-3460 FAX: 706-824-7501 www.mmsystemscorp.com		RIGHTS OF DESIGN		SP-SS-2-1_FPF	
		All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.		Model:	Scale:
				Drawn by: LMP	NTS
For Spec-Data, Installation Guides, or movement requirements, contact MMSC		SHT. . OF .		Issue Date: 11-16-12	