

- 1		Nominal	Joii	ոt Opening "J⁻	Γ"		Total	Mat.
	Model	"JT"	Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.	Movement	Code
	VSS-400-I_CONC_2HWPF_SS	4" (102)	1.75" (44)	3" (76)	5" (127)	6" (152)	4.25" (108)	VS1503

() IN MOVEMENT TABLE DENOTES mm IN METRIC.

ARCHITECT/CONTRACTOR NOTE:

IMPORTANT LIFE SAFETY NOTE

NOTE 2 BARRIERS REQUIRED. MINIMUM WALL DEPTH REQUIRED FOR RATING:

8.625" (219mm) FOR DUAL SIDE INSTALLATION

FABRICATION

ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative:

Approved by:	Date:					
SEAL NOTE: SPE	CIFY SEAL COLOR					
STANDARD COLORS: CARBON (BLACK) FOG (GRAY)	PRAIRIE (BEIGE)					
CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF.						
D : (N)						

MM SYSTEMS

Customer:

Project:

Location:

Project Number:

50 MM WAY PENDERGRASS, GA. 30567

PHONE: 706-824-7500 800-241-3460 FAX: 706-824-7501

www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

 $VSS-400-I_CONC_2HWPF_SS$

Drawn by: Scale: LMP NTS Issue Date: SHT. OF 03-06-13

Drawing Number: VS1503