
Model	Nominal		Nominal		Thermal Movement (JO _T)				Seismic Movement (JOs)				Total (JO∆)		Blockout Width	
Number	(10 ⁿ)		(SL _N)		Minimum		Maximum		Minimum		Maximum		Movement		(BW)	
ABC-C-250	1.75	45	4.000	102	0.750	19	2.50	64	0.75	19	3.25	83	2.50	64	3.500	89
ABC-C-350	2.50	64	5.000	127	1.000	25	3.50	89	1.00	25	4.25	108	3.25	83	4.500	114
ABC-C-450	3.00	76	6.000	152	1.500	38	4.50	114	1.50	38	5.50	140	4.00	102	5.000	127
ABC-C-550	4.00	102	7.000	178	1.500	38	5.50	140	1.500	38	6.50	165	5.000	127	6.000	152

7

SEAL PROFILES

250 SEA

Dimension shown in inches (bold) and millimeters. JO = Joint Opening. SL = Sight Line. Color Options for rubber seals are Black or Special Order Gray. Elevation Tolerence-Surface areas two feet on each side of the expansion joint opening shall have identical elevations creating flush slab-to-slab transition.



ABC Series Expansion Joint

(Slab-to-Wall)



50 MM WAY PENDERGRASS, GA. 30567 706-824-7500 PHONE 800-241-3460 TOLL FREE 706-824-7501 FAX

www.mm-usa.com

For Spec-Data, Install Guides and other data visit www.mm-usa.com.

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Armored Bolt-Down Cover Strip Expansion Joint ABC-C Series/Recessed Cover

Drawn by:	Scale:				
DMW	NTS				
SHT. 1 OF 1	Issue Date: 03-10-2016				

Drawing Number:

31875-04