



0.875" [22mm] DIA LOAD TRANSFER HOLES
@ 1.25" [32mm] O.C.

LOKCRETE ELASTOMERIC CONCRETE

0.75" *
[19mm]

3.50"
[89mm]

IMPACT DAMPING BULK HEAD
WITH C-LOK DESIGN

60 MIL 1" MICROWATERSEAL TAPE

0.25" (6mm) X 1.75" (44mm)
CONCRETE ANCHOR
@ 18" (457mm) O.C.

1.875"
[48mm]

30 MIL X 2" MICROWATERSEAL TAPE

2.75"
[70mm]

* IMPORTANT DIMENSION - ACHEIVE
REQUIRED DEPTH BY EXACT FORMING,
GRINDING, MILLING OR LEVELING BED

0.75" [19mm] Minimum
1.75" [44mm] Nominal
2.50" [64mm] Maximum
Thermal & Seismic

LMS-C-250 Expansion Joint (Slab-to-Wall)



50 MM WAY
PENDERGRASS, GA. 30567
706-824-7500 PHONE
800-241-3460 TOLL FREE
706-824-7501 FAX

www.mm-usa.com

For Spec-Data, Install Guides and other data visit www.mm-usa.com.

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

LokCrete Membrane Seal Expansion Joint LMS-C 250 Series

Drawn by: DMW	Scale: NTS	Drawing Number:
SHT. 1 OF 1	Issue Date: 05-02-2018	30100-08