
Model	Nominal		Nominal		Thermal Movement (JO _T)				Seismic Movement (JOs)				Total (JO△)		Cover Width	
Number	(10 ⁿ)		(SL _N)		Minimum		Maximum		Minimum		Maximum		Movement			
SCG-C-600	6.00	152	0.11	279	1.00	25	9.00	229	0.25	6	9.00	229	8.75	222	11.00	279
SCG-C-800	8.00	203	14.00	356	1.00	25	12.00	305	0.25	6	12.00	305	11.75	298	14.00	356
SCG-C-1000	10.00	254	17.00	432	1.00	25	15.00	381	0.25	6	15.00	381	14.75	375	17.00	432
SCG-C-1200	12.00	305	20.00	508	1.00	25	18.00	457	0.25	6	18.00	457	17.75	451	20.00	508

Dimension shown in inches (bold) and millimeters. JO = Joint Opening. SL = Sight Line. Color Options for rubber seals are Black or Special Order Gray. Waterproofing Membrane Compatibility - confirm with membrane manufacturer grade of rubber to be used on waterproofing splice flap.



M M SYSTEMS 50 MM WAY PENDERGRASS, GA. 30567 706-824-7500 PHONE 800-241-3460 TOLL FREE 706-834-7501 FAX

www.mm-usa.com

For Spec-Data, Install Guides and other data visit www.mm-usa.com.

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Split Slab Covered Gutter Expansion Joint

SCG-C Series with Aluminum Base Angles

Drawn by:	Scale:				
DMW	NTS				
SHT. 1 OF 1	Issue Date: 08-02-2016				

Drawing Number:

41275-02