
| Model    | Nominal |     | Nominal            |     | Thermal Movement (JO <sub>T</sub> ) |     |         | Seismic Movement (JOs) |         |    | Total (JO∆) |     | Slide Plate |     | Blockout Depth |    | Centering Bar |    |        |     |
|----------|---------|-----|--------------------|-----|-------------------------------------|-----|---------|------------------------|---------|----|-------------|-----|-------------|-----|----------------|----|---------------|----|--------|-----|
| Number   | (IOv)   |     | (SL <sub>N</sub> ) |     | Minimum                             |     | Maximum |                        | Minimum |    | Maximum     |     | Movement    |     | Thickness (ST) |    | (BD)          |    | Length |     |
| STS-400  | 4.00    | 102 | 8.00               | 279 | 2.00                                | 51  | 6.00    | 152                    | 1.00    | 25 | 6.00        | 152 | 5.00        | 127 | 0.375          | 10 | 1.25          | 32 | 11.00  | 279 |
| STS-600  | 6.00    | 152 | 11.00              | 356 | 3.00                                | 76  | 9.00    | 229                    | 1.00    | 25 | 9.00        | 229 | 8.00        | 203 | 0.375          | 10 | 1.25          | 32 | 14.00  | 356 |
| STS-800  | 8.00    | 203 | 14.00              | 432 | 4.00                                | 102 | 12.00   | 305                    | 1.00    | 25 | 12.00       | 305 | 11.00       | 279 | 0.375          | 10 | 1.25          | 32 | 17.00  | 432 |
| STS-1000 | 10.00   | 254 | 17.00              | 508 | 5.00                                | 127 | 14.00   | 356                    | 1.00    | 25 | 15.00       | 381 | 16.00       | 406 | 0.375          | 10 | 1.25          | 32 | 20.00  | 508 |
| STS-1200 | 12.00   | 305 | 20.00              | 584 | 6.00                                | 152 | 12.00   | 305                    | 1.00    | 25 | 18.00       | 457 | 17.00       | 432 | 0.500          | 13 | 1.25          | 32 | 23.00  | 584 |

Dimension shown in inches (bold) and millimeters. JO = Joint Opening. SL = Sight Line. Color Options for rubber seals are Black or Special Order Gray.





50 MM WAY PENDERGRASS, GA. 30567 706-824-7500 PHONE 800-241-3460 TOLL FREE 706-824-7501 FAX

www.mm-usa.com

For Spec-Data, Install Guides and other data visit www.mm-usa.com.

## RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

## Seismic Top Mount Slide Plate Expansion Joint STS Series

| Drawn by: | Scale: |                           |  |  |  |  |  |
|-----------|--------|---------------------------|--|--|--|--|--|
| DMW       | NTS    |                           |  |  |  |  |  |
| SHT. 1 OF | 1      | Issue Date:<br>05-13-2016 |  |  |  |  |  |

31325-01

Drawing Number: