



EX-K SYSTEM

SPECC DATA
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

DESCRIPTION

EX-K systems are made up of aluminum covers with a supporting isolation gasket factory installed. Steel clips are secured with appropriate anchors.

BASIC USE

EX-K systems are used for covering expansion joint openings in walls and ceilings and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Installation is easy
- Sightline is very crisp
- Easy maintenance

FINISH

204-R1 clear anodized finish

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of

the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Steel conforms to ASTM A569 for commercial quality sheet and plate.
- 204-R1 conforms to AA-M10C22A31.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399 for cycling joint.