



FLUSHLINE SYSTEMS

DESCRIPTION

Flushline systems are made up of frames, support slide, and elastomeric joint filler (PVC) or frames and elastomeric joint filler (PVC).

BASIC USE

Flushline systems are used for covering expansion joint openings and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Installation is easy
- Seal can be installed later on most systems if necessary.
- The seal is available in many colors
- Floor systems are available in a wide range of heights to accommodate different material thicknesses.
- Floor and wall systems may be fire rated.

LIMITATIONS

Floor to floor systems are intended for pedestrian traffic only. Concentrated wheel loading is not advised.

COLOR OPTIONS

Standard:

Lunar White, Prairie, Fog, Carbon

Non-Standard:

Heather, Madrid, Slate, Statuette

FINISH

Aluminum frames and support slides are mill finish.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloy 6063-T5.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399

MM Systems Corporation reserves the right to amend or withdraw information contained herein, without notice, and will not be liable for any inaccuracy or ambiguity of said information.

Current Issue: 3-18-03