



LSSBE-NB SYSTEMS

SPEC DATA
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

DESCRIPTION

LSSBE-NB systems consist of aluminum frame, stainless steel side plate, stainless steel cover plate along with appropriate fasteners and anchors.

BASIC USE

LSSBE-NB systems are used for covering expansion joint and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Heavy-duty to handle continuous pedestrian and light carts.
- Blockout height is shallow

LIMITATIONS

- Not for forklift or heavy concentrated wheel loads.
- The family of No-Bump (NB and NBR) must only be used in climate control 24/7 environments due to the limited thermal movement.

FINISH

All exposed aluminum is mill finish. Side plate and cover plate are stainless steel.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Stainless Steel conforms to ASTM A480 for sheet and plate.
- Conforms to ASTM E1399 for cycling joint.