



# RXH & RXJ SYSTEMS

## DESCRIPTION

RXH & RXJ systems consist of aluminum frame, cover plate along with appropriate fasteners and anchors.

## BASIC USE

RXH & RXJ systems are used for covering roof expansion joint openings, maintaining watertight integrity of the roof and providing a clean and aesthetically pleasing sightline where the joints occur.

## FEATURES

- Have seismic centering bars.
- Cover plates can be engineered to resist snow and wind loads.
- Color and anodizing is available.

## LIMITATIONS

Not designed for heavy concentrated wheel loads.

## FINISH

All exposed aluminum is mill finish.

## STORAGE

All materials should be stored in a cool, dry location prior to use.

## INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation guide.

## LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

## TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Steel conforms to ASTM A569 for commercial quality sheet and plate.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399 for cycling joint.