



# **XM and XN SYSTEMS**

## **DESCRIPTION**

X-M and X-N systems are made up of aluminum covers with a supporting isolation gasket factory installed. The cover is secured with appropriate anchors.

## **BASIC USE**

X-M and X-N systems are used for covering expansion joint openings in walls and ceilings and providing a clean and aesthetically pleasing sightline where the joints occur.

## **FEATURES**

- Installation is easy
- Sightline is very crisp
- Easy maintenance

## **FINISH**

204-R1 clear anodized finish

## **STORAGE**

All materials should be stored in a cool, dry location prior to use.

## **INSTALLATION**

Apply to clean, dry, sound substrate. See manufacturer's standard installation instructions.

## **LIMITED WARRANTY**

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of

the product.

## **TECHNICAL DATA**

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- 204-R1 conforms to AA-M10C22A31.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399 for cycling joint.